



ООО «Ремстанмаш» 214000, г. Смоленск, улица Верхне - Сенная улица, дом 4, офис № 402 Тел.: 8-800-511-02-67 http://www.cnchelp.ru


Installing structure of the unit

TTC400A cable tool setter unit is a product specially developed by our company for replacing some vulnerable tool setting units that is part of the swing-arm for setting the cutting tool in the CNC lathes; The structure and size of the installing parts are exactly the same as the replacement, and the output signal is exactly the same.











Technical Parameters

The diameter of the four ceramic touching pillar(for cutting tool touching):
5.0 mm; the pillars' hardness : HM8.5;

- Sensing direction of the pillars: $\pm X$, $\pm Z$;
- The pillars sensing over-travel : X-Z±5 mm;
- The trigger repeatability of the pillar(2σ): $\leq 2 \mu m$;
- Input voltage is $24 \pm 10\%$ V DC and output load current is 50 mA;

◆ Signal model and LED instruction: high electric level output with normal signal state, LED normally on; When any one pillar is triggered, the signal output point is suspended and the LED is off;

Seal grade: IP68.

Technical Characteristics

♦ As shown in the picture, the installing structure and size of the tool setter unit are exactly the same as the replacement;

- Tool setter unit transmits tool setting signal through cable;
- ♦ It is ensured during manufacturing that the position relationship between four pillars of the tool setter unit and mounting base;

One LED indicator light is used to display the tool setter's working state.

Application

- Set parameters of cutting tools automatically before CNC processing;
- Detect wear and breakage of cutting tools automatically between two processes or after the CNC processing;

◆ Through checking cutting tool parameters to control the change of machining precision from the temperature change of the machine;

◆ Applicable equipments: various specifications of CNC lathe, turning machine center and CNC milling -turning center;

◆ The cable: TTC400A tool setter unit is equipped a 6 meter-long, three-core, anti-oil shielded cable.

Notes for purchase

◆As for the cable length, verify whether the cable length equipped is enough for installing the tool setter unit on your machine tool; If lengthening cable is needed, special instructions should be given when ordering the product;